



# VK1618 Datasheet

8×4/7×5/6×6/5×7 LED DRIVER

Rev.1.3

## Intellectual Property Statement:

Shenzhen Vinka Microelectronics Co., Ltd. (hereinafter referred to as “the Company”) owns legally registered intellectual property rights in both domestic and international jurisdictions. Any unauthorized use of the Company’s products or patented technologies by individuals or organizations is strictly prohibited.

The Company reserves the right to take legal action against any infringement, and to seek full compensation for damages or unlawful gains.

The Company’s name and trademarks are legally protected and may not be used or imitated without explicit written permission. No implied or express license shall be granted under any circumstances.

## 1 General Description

VK1618 is a dedicated chip for digital tube or dot matrix LED driver control with a keyboard scanning interface. It integrates a 3-wire serial interface, data latch, LED driver, keyboard scanning and other circuits internally. The SEG pin is connected to the anode of the LED, and the GRID pin is connected to the cathode of the LED. It can support 8SEG×4GRID, 7SEG×5GRID, 6SEG×6GRID, and 5SEG×7GRID dot matrix LED display panels, with a maximum support of 5×1 keys. It is suitable for products that require reliability, stability and strong anti-interference ability.

## 2 Key Features

- Operating voltage: 3.0-5.5V
- Built-in RC oscillator
- 5 SEG pins, 4 GRID pins, and 3 configurable SEG/GRID multiplexing pins
- The SEG pin can only be connected to the anode of the LED, and the GRID pin can only be connected to the cathode of the LED
- 5×1 matrix keys, supporting simultaneous pressing of multiple keys (Key/display multiplexing requires the coordination of hardware circuits)
- 3-wire serial interface
- The overall brightness is adjustable at 8 levels
- The built-in display RAM is 14×8 bits
- Built-in power-on reset circuit
- Strong anti-interference ability
- Available Packages:  
SOP18 (300mil)(11.45mm×7.50mm PP=1.27mm)

## 3 Application Field

- Small household appliances
- Induction cooker/microwave oven
- Pressure gauge

## 4 Product Selection


Part No.	Common Cathode Drive	Common Anode Drive	Key press	Packaging
VK1616	7 / 4	4 / 7	---	SOP16
VK1618	5 / 7, 6 / 6 7 / 5, 8 / 4	7 / 5, 6 / 6 5 / 7, 4 / 8	5×1	SOP18
VK1620	8 / 6, 9 / 5 10 / 4	6 / 8, 5 / 9 4 / 10	---	SOP20
VK1624	11 / 7, 12 / 6 13 / 5, 14 / 4	7 / 11, 6 / 12 5 / 13, 4 / 14	---	SOP24
VK1S68C	10 / 7, 11 / 6 12 / 5, 13 / 4	7 / 10, 6 / 11 5 / 12, 4 / 13	10×2	SSOP24
VK1Q68D	10 / 7, 11 / 6 12 / 5, 13 / 4	7 / 10, 6 / 11 5 / 12, 4 / 13	10×2	QFN24L (4mm*4mm)
VK1668	10 / 7, 11 / 6 12 / 5, 13 / 4	7 / 10, 6 / 11 5 / 12, 4 / 13	10×2	SOP24
VK1628	10 / 7, 11 / 6 12 / 5, 13 / 4	7 / 10, 6 / 11 5 / 12, 4 / 13	10×2	SOP28
VK1628A	10 / 7, 11 / 6 12 / 5, 13 / 4	7 / 10, 6 / 11 5 / 12, 4 / 13	10×2	SSOP28

Note: For both common cathode and common anode digital tubes, SEG is connected to the anode and GRID to the cathode.

## 5 Ordering Information

Part No.	Packaging	Tube Qty	Tray(reel) Qty	Box Qty	Total Qty	Notes
VK1616	SOP16	50/tube		10000/box	100000 PCS	
VK1618	SOP18					
VK1620	SOP20	36/tube		2880/box	28800 PCS	
VK1624	SOP24	30/tube		2400/box	24000 PCS	
VK1S68C	SSOP24	50/tube		10000/box	100000 PCS	
VK1Q68D	QFN24L (4mm*4mm)		3000/reel		24000 PCS	reel
VK1668	SOP24	30/tube		2400/box	24000 PCS	
VK1628	SOP28	26/tube		2080/box	20800 PCS	
VK1628A	SSOP28	50/tube		5000/box	50000 PCS	

## 6 Package Pinout Information(SOP18)




For more information: [Page 18](#)

## 6.1 VK1618/SOP18 Pin Description

No.	Name	I/O	Function
1	DIO	I/O	Bidirectional data (NMOS open leakage), data input/output starts from the lower bit. Read the DIO pin data to the visible RAM at the rising edge of the clock and output the data to the DIO pin at the falling edge of the clock.
2	CLK	I	The clock signal reads DIO pin data to the display RAM at the rising edge and outputs data to the DIO pin at the falling edge
3	STB	I	Chip selection signal, high level disabled, low level enabled
4	K2	I	Key scanning input, the key signal is latched after the display cycle ends
5	VDD	VDD	Positive power supply
6-10	SEG1/KS1- SEG5/KS5	O	LED SEG output (P-channel); Key scan output.
11, 12 13	SEG12/GRID7- SEG14/GRID5	O	LED SEG/GRID multiplexing output can be configured as either SEG output or GRID output through software
14, 15 17, 18	GRID4-GRID1	O	LED GRID output (N-channel open-drain output)
16	GND	GND	Negative power supply

## 7 Functional Description

### 7.1 Block Diagram



## 7.2 Display RAM- Storage Structure

The static display memory (RAM) has a structure of 14×8 bits and stores the displayed data. The content of RAM is directly mapped to the display content of the LED driver, with the display address ranging from 0xC0 to 0xCD, and there are a total of 14 display units. If you want to turn on or off a certain LED, simply set the corresponding display RAM position 1 or clear 0. For example, to control the on/off of LED1 driven by pins SEG1 and GRID1, simply set the bit0 position of the corresponding display RAM (address 0xC0) to 1 or clear 0. Clear the RAM bits corresponding to the unused SEG pins in the application to 0.

The process of mapping the contents in RAM to LED is shown in the following table:


SEG	X	X	SEG14	SEG13	SEG12	X	X	X	Addr	X	X	X	SEG5	SEG4	SEG3	SEG2	SEG1	Addr	SEG
GRID																			GRID
GRID1									0xC1								1	0xC0	GRID1
GRID2									0xC3									0xC2	GRID2
GRID3									0xC5									0xC4	GRID3
GRID4									0xC7									0xC6	GRID4
⋮									⋮									⋮	⋮
GRID7									0xCD									0xCC	GRID7
	D7	D6	D5	D4	D3	D2	D1	D0		D7	D6	D5	D4	D3	D2	D1	D0		

Note:

1. The value stored inside the chip display RAM at the moment of power-on may be random. It is recommended that the customer perform a power-on reset of the display RAM, that is, write all the data 0x00 to the 14-byte display RAM (address 0xC0-0xCD) after power-on.
2. The SEG pin can only be connected to the anode of the LED, and the GRID pin can only be connected to the cathode of the LED. They must not be reversed.

## 8 Key Scanning

### 8.1 Key Data Reading



The key scanning is automatically completed by the hardware. Users only need to read the key values in sequence. It takes two display cycles to complete one key scan, with each display cycle approximately taking 4ms. Within 8ms, two different keys were pressed successively, and the key values read twice were those of the first pressed key.


After the host sends the command to read the key, it starts to read the 3-byte key data in sequence. The read key data is output from the lower bit. When a certain key is pressed, the bit position within the corresponding key data byte is 1.

Key data	X	X	X	K2	X	X	K2	X
Byte 1	0	0	0	K2/KS2	0	0	K2/KS1	0
Byte 2	0	0	0	K2/KS4	0	0	K2/KS3	0
Byte 3	0	0	0	0	0	0	K2/KS5	0
	D7	D6	D5	D4	D3	D2	D1	D0


Note: Reading key data must be done in sequence. Cross-byte reading is not allowed, and the reading should not exceed 3 bytes.

## 8.2 Key Scan Timing

The key scanning and display sequence diagram is as follows:




### 8.3 Key/Display Reuse



As shown in the above figure, for LED1 to be on and LED2 to be off, SEG1 needs to be in the "0" state and SEG2 in the "1" state. If KEY1 and KEY2 are pressed simultaneously, it is equivalent to SEG1 and SEG2 being short-circuited. At this time, both LED1 and LED2 will be on. This can be solved by connecting diodes in series.

As shown in the following figure:



## 9 Serial Communication Commands

### 9.1 Communication Interface

3 lines are required to interface with the VK1618.

STB is the chip select pin. it is used to enable / disable communication with the controller, high level disable(prohibits and initializes internal timing), low level enables. The first byte input by the DIO pin after the falling edge of the STB is used as the command. If the STB is set to high level during instruction or data transmission, the serial communication is initialized and the command or data being transmitted is invalid.

CLK is the clock signal pin. It reads the data of DIO pin to display RAM on the rising edge and outputs the data to DIO pin on the falling edge.

DIO is the Bidirectional data pin. It used to read / write data or write commands . it is an NMOS open drain output and needs to connect a resistor. with VDD.

### 9.2 Command Format

Commands are used to set the display mode, write display data and read key values.

The first byte input by DIO after the falling edge of STB is taken as the command. After decoding, the highest two bits, 7 and 6, are selected to distinguish different commands, as shown in the following table:

Bit7	Bit6	Command function
0	0	Display mode setting command
0	1	Data read and write setting command
1	0	Display control command
1	1	Address setting command

## 10 Command Description

### 10.1 Display Mode Setting Command

Set the number of segments and bits for LED display (4 to 7 bits, 5 to 8 seg). When this command is executed, the display is forcibly turned off. If the same mode setting is selected, the command will not be executed. When powered on, set the mode to 7-bit, 5-seg.

Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0	Display mode
0	0	---				0	0	8-seg 4-bit
0	0	---				0	1	7-seg 5-bit
0	0	---				1	0	6-seg 6-bit
0	0	---				1	1	5-seg 7-bit

### 10.2 Data Read And Write Setting Commands

This command is used for LED display data writing and key reading as well as related commands. Bit1 and Bit0 bits are not allowed to be set to 01 or 11. When powered on, the Bit3-Bit0 data is 0.

Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0	Function	Note
0	1	---				0	0	Data read and write mode settings	Write the data to the display register
0	1	---				1	0		Read the key data
0	1	---			0			Address increase mode settings	address increases automatically
0	1	---			1				Fixed address
0	1	---		0				Working mode settings	Normal mode
0	1	---		1					Test mode

### 10.3 Address Setting Command

Set the address of the displayed RAM (0xC0-0xCD). When powered on, the address is set to 0xC0 by default.


Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0	Display the RAM address
1	1	---		0	0	0	0	0xC0
1	1			0	0	0	1	0xC1
1	1			0	0	1	0	0xC2
1	1			0	0	1	1	0xC3
1	1			0	1	0	0	0xC4
1	1			0	1	0	1	0xC5
1	1			0	1	1	0	0xC6
1	1			0	1	1	1	0xC7
1	1			1	0	0	0	0xC8
1	1			1	0	0	1	0xC9
1	1			1	0	1	0	0xCA
1	1			1	0	1	1	0xCB
1	1			1	1	0	0	0xCC
1	1			1	1	0	1	0xCD

### 10.4 Display Control Command

Set the display switch and select the display brightness (8 levels).

Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0	Function	Note
1	0	---			0	0	0	Set the pulse width	Set the pulse width to 1/16
1	0				0	0	1		Set the pulse width to 2/16
1	0				0	1	0		Set the pulse width to 4/16
1	0				0	1	1		Set the pulse width to 10/16
1	0				1	0	0		Set the pulse width to 11/16
1	0				1	0	1		Set the pulse width to 12/16
1	0				1	1	0		Set the pulse width to 13/16
1	0				1	1	1		Set the pulse width to 14/16
1	0		0				Display switch	Show off	
1	0		1					Display on	

## 10.5 Command Timing




## 11 Command Application

### 11.1 Send Display Data (address automatically adds 1)

To transfer display data using the address auto-increment mode, first set the starting address of the data to be transferred (corresponding to the display RAM address).

After the starting address command word is sent, the STB does not need to be set high and can directly transmit the display data, with a maximum of 14 bytes. Until the last byte of display data is transmitted, the STB is set high.



Cmd1: Display Mode Setting Command - Set the number of segments and bits selected for LED display (can be set during initialization)

Cmd2: Data Read and Write Settings Command - Set Address Auto-increment (0x40)

Cmd3: Address Setting Command - Set the display RAM starting address (0xC0-0xCD)


Data1-Datan: Send the display data to the starting address set by Cmd3 and the subsequent display RAM (up to 14 bytes)

Cmd4: Display Control Commands - Display on and set the display brightness level

Note: When writing data, the RAM address is automatically increments by 1, and zeros are sent between discontinuous addresses for padding.

## 11.2 Send Display Data (fixed address)

To transfer display data using the fixed address mode, first set the address of the data to be transferred (corresponding to the display RAM address). After the address is sent, the STB does not need to be set high and can directly transfer 1 byte of display data. After the data is transferred, the STB is set high. Send the address of the next display data. The STB does not need to be set high and can directly send 1 byte of display data. After the data is transmitted, the STB is set high. ... Display the data until the last byte is transmitted, with a maximum of 14 bytes.



Cmd1: Display Mode Setting Command - Set the number of segments and bits selected for LED display (can be set during initialization)

Cmd2: Data Read and Write Settings Command - Set Fixed Address Mode (0x44)

Cmd3: Address Setting Command - Set Display RAM Address (0xC0-0xCD)

Data1: Send display data to the display RAM address set by Cmd3


Cmd4: Address Setting Command - Set Display RAM Address (0xC0-0xCD)

Data2: Send display data to the display RAM address.... set in Cmd4 A maximum of 14 bytes of data can be transmitted

Cmd5: Display Control Commands - Display on and set the display brightness level

## 11.3 Read The Key Data

The data read and write setting command is set to read key data, and then sequential reading of 3-byte key data begins. The read key data is output starting from the lower bit.




Cmd1: Display Mode Setting Command - Set to read key data (0x42)

Data1-Data5: Sequentially read 3-byte key data, and output the key data starting from the lower bit.



## 12 Application Circuits

When the surrounding interference is relatively large, a 10R to 10k resistor and a PF-class small capacitor to ground can be connected in series on the communication pin

When the power supply for the single-chip microcomputer (3.3V) and the driver chip (5V) is inconsistent, it is recommended to add a level conversion circuit to the communication pin



The filter capacitor between VDD and GND should be placed as close to the chip as possible on the PCB board to enhance the filtering effect.



The VK1618 features multiple display modes and the number of segments and bits can be set by software: 5 segments with 7 bits, 6 segments with 6 bits, 7 segments with 5 bits, and 8 segments with 4 bits  
Connect the SEG pin to the anode of the LED and the GRID pin to the cathode of the LED

## 13 Electrical Characteristics

### 13.1 Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Supply voltage	VDD	-0.3~7.0	V
Input voltage	VIN	$V_{SS}-0.5 \sim V_{DD}+0.5$	V
Power loss	PD	400	mW
Drive output current	$I_{OLGRID}$	+250	mA
	$I_{OHSEG}$	-50	mA
Storage temperature	$T_{STG}$	-50~+125	°C
Operating temperature	$T_{OTG}$	-40~+85	°C

### 13.2 DC Electrical Characteristics


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions	
						VDD	Conditions
Operating voltage	VDD	3.0	—	5.5	V	—	—
Static current	$I_{DD}$	—	0.5	1.0	mA	5V	No load /LED off
High-level output current	$I_{OHSEG1}$	-20	-25	-40	mA	5V	VO=VDD-2V SEG1- SEG7
	$I_{OHSEG2}$	-25	-30	-50			VO=VDD-3V SEG1- SEG7
Low-level input current	$I_{OLGRID}$	100	140	—	mA	5V	VO=0.3V GRID1- GRID4
High-level output current tolerance	$I_{TOLSEG}$	—	—	5	%	VDD	VO=VDD-3V(VDD=5V) VO=VDD-2V(VDD=3V) SEG1 to SEG7
Low-level Input	$V_{IL}$	0	—	0.3	VDD	VDD	STB, CLK, DIO
High-level Input	$V_{IH}$	0.7	—	1.0		VDD	
Pull-down resistor	$R_L$	—	—	—	kΩ	5V	—

### 13.3 AC Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Transmission delay time	$t_{PLZ}$	—	—	300	nS	CLK → DOUT
	$t_{PZL}$	—	—	100	nS	CL = 15pF, RL = 10KΩ
Rising time	$t_{ZH1}$	—	—	2	μS	CL=300pF SEG1-SEG5
	$t_{ZH2}$	—	—	0.5	μS	CL=300pF GRID1-GRID4 SEG12/GRID7-SEG14/GRID5
fall time	$t_{THZ}$	—	—	1.5	μS	CL=300pF SEGn,GRIDn
Maximum input clock frequency	$F_{MAX}$	—	—	1	MHz	Duty cycle: 50%
Input capacitance	$C_1$	—	—	15	pF	—

## 14 Package Information

### 14.1 SOP18 (300mil)(11.45mm × 7.50mm PP=1.27mm)



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	-	-	2.65
A1	0.10		0.30
A2	2.20	2.30	2.40
A3	0.97	1.02	1.07
b	0.35	-	0.43
b1	0.34	0.37	0.40
c	0.25	-	0.29
c1	0.24	0.25	0.26
D	11.35	11.45	11.55
E	10.10	10.30	10.50
E1	7.40	7.50	7.60
e	1.27BSC		
L	0.70	-	1.00
L1	1.40REF		
h	0.25	-	0.75
$\theta$	0	-	8°

## 15 Disclaimer

**Warranty and liability** — The information provided in this document is believed to be accurate and reliable. However, Shenzhen Vinka Microelectronics Co., Ltd. (hereinafter “the Company”) makes no warranties, express or implied, as to the completeness or suitability of this information for any specific purpose.

In no event shall the Company be liable for any indirect, incidental, or consequential damages, including but not limited to loss of profits, equipment damage, or system failure, arising out of the use of this product or documentation, regardless of the legal theory under which such liability is asserted.

**Right to change** — The Company reserves the right to modify any information contained herein without prior notice. The latest version of this document is available at:

<https://www.szvinka.com/>

**Applicability** — This product is not designed or intended for use in life-critical, medical, or safety systems where failure could result in injury or death. The customer shall assume full responsibility for any such use.

**Application** — All product application descriptions provided herein are intended for illustrative purposes only. The Company makes no representations or warranties, express or implied, regarding the suitability of any specific application without further testing or modification.

The customer is solely responsible for determining whether the Company’s products are appropriate for their intended applications or end customers.

The customer shall ensure proper design practices, implementation safeguards, and operational validation to minimize risks associated with product use.

The Company shall not be held liable for any defects, losses, costs, or damages arising from weaknesses or failures in the customer’s own products or applications, or from the integration or use of third-party products.

Furthermore, the customer shall conduct all necessary testing and validation for any third-party deployment of the Company’s products to avoid potential misuse or associated damages. The Company assumes no liability in this regard.

**Commercial terms of sale** — Unless otherwise agreed in writing, sales of this product are subject to the Company’s standard terms and conditions of sale. The Company expressly rejects the applicability of the customer’s general terms and conditions.

**Export control** — This product may be subject to applicable export control regulations. The customer is solely responsible for compliance with such regulations, including obtaining any necessary export licenses.

## 16 Revision History

No.	Version	Date	Modify the content	Check
1	1.0	2018-08-10	Initial release	YES
2	1.1	2018-10-11	Add reference circuit	YES
3	1.2	2019-03-21	Alignment correction	YES
4	1.3	2025-09-09	Change Description	YES

[1] Please refer to the latest version of this document before starting or finalizing any design.

[2] Since the release of this document, the status or availability of this product may have changed. For the most up-to-date information, please visit:

<https://www.szvinka.com/>